

Mod. 3110HL.B

3110HL – EXPLORER CASES, ULTRALIGHT WATERPROOF CASE

COMING SOON

Small size watertight case, injected with proprietary copolymer PP that makes it more resistant and lightweight than other similar products.


IP67 and MIL Stan certified to be resistant to impact, liquids, shocks.

- Metal reinforced padlock holes
- Single block high performance injected O-ring
- Manual pressure release valve
- Soft rubber handle grip
- Certified to grant constant performances between -33°C and +90 °C.

* Pending certification release



METRIC MM-KG-C°

**INTERNAL DIMENSIONS**

L LENGTH	310 mm
W WIDTH	100 mm
D DEPTH	108 mm
LID	20 mm
BASE	88 mm

EXTERNAL DIMENSIONS


L LENGTH	336 mm
W WIDTH	159 mm
D DEPTH	127 mm

OTHER DATA

WEIGHT EMPTY	0.95 Kg
WEIGHT WITH FOAM	1.05 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	3.4 lt
BUOYANCY	2.5 Kg/max

TEMPERATURE

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS

L LENGTH	12 3/16 in
W WIDTH	3 15/16 in
D DEPTH	4 1/4 in
LID	13/16 in
BASE	3 7/16 in

EXTERNAL DIMENSIONS

L LENGTH	13 1/4 in
W WIDTH	5 1/4 in
D DEPTH	5 in

OTHER DATA

WEIGHT EMPTY	2.09 lbs
WEIGHT WITH FOAM	2.31 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	0.89 gal
BUOYANCY	5.51 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max 194

FEATURES



CORROSION PROOF METAL HINGES WITH LID STAY FEATURES



INTERNAL SLOTS

Internal slots for optional panel mounting brackets or panel mounting rings



SEALING O-RING

(Art. NEOSEAL + nr. art.)



MANUAL PRESSURE RELEASE VALVE

The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



PVC WATERPROOF I. D. REMOVABLE LABEL

(Art. LABELCOVER + nr. art.)



COUNTERBALANCE SUPPORTS

(in certain models)

ACCESSORIES



PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

EXPL PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



PATENTED COMBINATION PADLOCK

EXPL COMBILOCK

Designed to fit snug to the Explorer case mould so as not to swing out



BLIND INSERT

KIT.EXPL.PLUGS

Kit includes 6 pcs. Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



TSA APPROVED PADLOCK WITH COMBINATION

EXPL TSA.DIGILOCK

The new TSA approved padlocks allow tsa® airport security agents to open the case without destroying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.



METAL BRACKET

KIT SUPP.EXPL.

Kit includes 6 pcs. All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly